

# Product data sheet

# Perlän 140 set for glass leaves



Sliding door fitting for glass leaves and ceiling installation

#### AREAS OF APPLICATION

- For ceiling and wall mounting
- For leaf weights up to 80 kg

# Perlan 140 set for glass leaves



## PRODUCT FEATURES

→ Sliding door fitting for ceiling installation and glass leaf with leaf weight up to 80 kg

## TECHNICAL DATA

|                            |                                 |
|----------------------------|---------------------------------|
| Productname                | Perlan 140 set for glass leaves |
| Corrosion protection class | 2                               |
| Glass thickness            | 8 - 12.76 mm                    |
| Colour                     | EV1                             |

## VARIANTS / ORDER INFO

| Designation                     | Description  | Ident-No. | Colour                | Leaf width (min.) | Leaf width (max.) |
|---------------------------------|--|-----------|-----------------------|-------------------|-------------------|
| Perlan 140 set for glass leaves | For ceiling installation with glass clamping plate individual cover and Perlan SoftStop, up to 80 kg leaf weight. Perlan SoftStop one-sided, with 2450 mm track on both sides. | 134858    | Stainless steel optic | 900 mm            | 1240 mm           |
| Perlan 140 set for glass leaves | For ceiling installation with glass clamping plate individual cover and Perlan SoftStop, up to 80 kg leaf weight. Perlan SoftStop one-sided, with 2450 mm track on both sides. | 134857    | Stainless steel optic | 575 mm            | 1000 mm           |
| Perlan 140 set for glass leaves | For ceiling installation with glass clamping plate individual cover and Perlan SoftStop, up to 80 kg leaf weight. Perlan SoftStop one-sided, with 2450 mm track on both sides. | 134851    | EV1                   | 575 mm            | 1000 mm           |
| Perlan 140 set for glass leaves | For ceiling installation with glass clamping plate individual cover and Perlan SoftStop, up to 80 kg leaf weight. Perlan SoftStop one-sided, with 2450 mm track on both sides. | 134852    | EV1                   | 900 mm            | 1240 mm           |

## PART

### FLOOR GUIDE FOR GLASS LEAF

Floor guide with variable adjustment for glass thicknesses 8, 10 and 12 mm



| Designation                             | Description  | Ident-No. | Colour          | Glass thickness |
|---|--|-----------|-----------------|-----------------|
| Floor guide for glass leaf (adjustable) | with variable adjustment for glass thickness 8-13.5 mm, with frieze band for noise reduction with structured glass surfaces, without attachment material | 120417    | silver-coloured | 8 - 13.5 mm     |

# Perlan 140 set for glass leaves



## END STOP PERLAN 140 (ALSO KS)

End stop for sliding leaves also suitable for outdoor use



| Designation                   | Description                         | Ident-No. |
|-------------------------------|-------------------------------------|-----------|
| End stop Perlan 140 (also KS) | Steel parts made of stainless steel | 119362    |

## END CAP PERLAN TRACK

End cap Perlan track



| Designation          | Ident-No. | Colour |
|----------------------|-----------|--------|
| End cap Perlan track | 119649    | black  |

## PERLAN SOFTSTOP SET, SHORT VERSION, DAMPED ON ONE SIDE, UP TO 80 KG

Perlan SoftStop damping on one side for leaf weights up to 80 kg and leaf widths of 575 to 900 mm



| Designation                          | Description   | Ident-No. | Leaf width (min.) | Leaf width (max.) |
|--------------------------------------|---|-----------|-------------------|-------------------|
| Perlan SoftStop set, short, one side | The set includes: 2 x roller carriage with damping unit on one side, 2 x end stop, 1 x trigger with fixing screw, 2 x standard suspension plate | 128876    | 575 mm            | 900 mm            |

# Perlan 140 set for glass leaves



## TRACK PERLAN 140

Track for sliding door fitting



| Designation      | Description   | Ident-No. | Colour                |
|------------------|---|-----------|-----------------------|
| Track Perlan 140 | with countersunk drill holes (prepared for Perlan SoftStop) | 142518    | EV1                   |
| Track Perlan 140 | with countersunk drill holes (prepared for Perlan SoftStop) | 128660    | EV1                   |
| Track Perlan 140 | with countersunk drill holes (prepared for Perlan SoftStop) | 128662    | Stainless steel optic |
| Track Perlan 140 | with countersunk drill holes (prepared for Perlan SoftStop) | 135061    | Stainless steel optic |
| Track Perlan 140 | with countersunk drill holes (prepared for Perlan SoftStop) | 135048    | EV1                   |
| Track Perlan 140 | with countersunk drill holes (prepared for Perlan SoftStop) | 135050    | Stainless steel optic |
| Track Perlan 140 | with countersunk drill holes (prepared for Perlan SoftStop) | 135049    | Stainless steel optic |
| Track Perlan 140 | with countersunk drill holes (prepared for Perlan SoftStop) | 135047    | EV1                   |
| Track Perlan 140 | with countersunk drill holes (prepared for Perlan SoftStop) | 142519    | EV1                   |
| Track Perlan 140 | with countersunk drill holes (prepared for Perlan SoftStop) | 135046    | EV1                   |