

Product data sheet

OL 360 EN *



Opening and locking system for outward opening bottom-hung, top-hung and side-hung windows

AREAS OF APPLICATION

- Natural ventilation (230 V) in the façade area
- Opening and locking of outward opening windows with bottom-hung, top-hung and side-hung leaves
- Installation on wooden, PVC or metal windows
- Leaf installation

PRODUCT FEATURES

- System solution with profile-mounted E 350 N spindle drive and a bracket set with locking device
- Mechanical locking at the main closing edge by the spindle drive
- Large opening width with small spindle stroke
- Only Solo operation possible

TECHNICAL DATA

Productname	OL 360 EN *
Space needed (min.)	Leaf frame: min. 33 mm, cover frame: min. 45 mm
Permissible dimensions of primary closing edge Solo for timber and aluminium frames	430 - 1200 mm
Permissible dimensions of primary closing edge Solo for plastic frames	430 - 800 mm
Leaf heights for Solo and Syncro	600 - 1600 mm
Force of pressure (max.)	750 N
Compressive force	750 N
Tensile force	750 N
Panel weight (max.)	30 kg/m ²
Voltage at operation	230 V ± 10 %
Operating voltage	230 V
Current consumption	0.15 A
Power consumption	35 W
Min. core cross section	1.5 mm ²
Number of cores	3 cores
Service temperature	-20 - 70 °C
IP rating	IP65
protection rating	II
Locking and additional angle bracket	Yes
End position cut-off extended	Electromechanical
End position cut-off retracted	Electromechanical
Overload cut-off	Yes
KNX ability	No
Bottom-hung window OUTWARD-opening leaf installation	Yes
Side-hung window OUTWARD-opening door leaf installation	Yes
Top-hung window OUTWARD-opening leaf installation	Yes

**VARIANTS / ORDER INFO**

Designation	Ident-No.	Colour	Stroke	Operating voltage
OL 360 EN	088055	EV1	150 mm	230 V
OL 360 EN	088070	white RAL 9016	300 mm	230 V
OL 360 EN	088058	white RAL 9016	150 mm	230 V
OL 360 EN	088067	EV1	300 mm	230 V
OL 360 EN	088060	EV1	200 mm	230 V
OL 360 EN	088064	white RAL 9016	200 mm	230 V

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.