


Product data sheet

A5001-FB *



Electric strike with door status contact and lock latch guide

AREAS OF APPLICATION

- Standard and smoke protection doors with swing door drives and access control
- Installation possible on left and right hand doors as well as horizontal or vertical
- Connection to direct or alternating current



PRODUCT FEATURES

- Approval for smoke protection doors
- Almost silent opening behaviour with direct current with one click
- Twin coil technology enables a larger operating voltage range
- Integrated bipolar EMC protective diode which protects connected electronic components against reverse voltage
- Door status contact, which is activated by the lock latch
- Compact dimensions
- Lock latch guide for installation in doors with closed profile edge

TECHNICAL DATA

Productname	A5001-FB *
Dimensions	22.8 x 64.6 x 27.7 mm
DIN direction	left / right
Set position x grid dimension	4 x 0.75 mm
Latch engagement depth	6.5 mm
Installation position vertical / horizontal	Yes
Fail-safe	No
Fail-secure	Yes
Dummy strike	No
Approval for smoke protection doors	Yes
Mechanical release	No
Door monitoring	Yes
Bipolar EMC protection diode integrated	Yes
Twin coil technology	Yes

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Dimensions	DIN direction
A5001-FB compact electric strike	Functional principle: fail-secure / with door status contact / with lock latch guide / Momentary contact: 12 - 48 V AC/DC / Continuous operation stability: 12 or 24 V AC/DC +/- 15% / Current consumption: 200 mA (at 12 V) / 100 mA (at 24 V)	180713	22.8 x 64.6 x 27.7 mm	left / right

A5001-FB *



* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.